## DTO1 Rec'd PCT/PTC 2 3 DEC 2004

Atty's 23150

10

11

12

1

Pat. App. Not known - US phase of PCT/EP2003/003532

## CLAIM AMENDMENTS

1. (currently amended) Cooking device characterised in that it comprises comprising:

a body which carries a bowl with electrical heating means and containing a basket for containing food to be cooked, said basket being connected to drive means suitable for moving it between a position inside said bowl and a position at least partially outside of it; , said device also comprising

a first sensor of the temperature of at least a portion of said bowl and a timer connected to means for controlling said drive means, for moving said basket, in relation to signals that said control means receives from said temperature sensor and from said timer and

means for stirring said food contained inside said basket and connected to said control means.

## 2. (Canceled)

3. (currently amended) Cooking device according to one or more of the previous claims claim 1, characterised in that said stirring means comprises an element rotatably connected to said basket and removably connected to a drive group which protrudes from said body and is connected to a first motor.

1

2

5

6

- 4. (currently amended) Cooking device according to one
  or more of the previous claims claim 3, characterised in that said
  rotatable element comprises a substantially conical disc, with a
  widened central portion rotatably connected in a through-seat
  realised on the base of said basket, said widened central portion
  defining a seat suitable for receiving said drive group.
- 5. (currently amended) Cooking device according to one
  or more of the previous claims claim 3, characterised in that said
  rotatable element comprises a shaft which has a central portion
  rotatably connected in a through-seat realised on the base of said
  basket, said central portion defining a seat suitable for receiving
  a portion of said drive group.
  - 6. (currently amended) Cooking device according to one or more of the previous claims claim 1, characterised in that said drive means comprises a support for said basket which has a rack operatively connected to a pinion which can be actuated through a second motor, said second motor being connected to said control means.
  - 7. (currently amended) Cooking device according to one or more of the previous claims claim 1, characterised in that it comprises at least one second sensor suitable for detecting the position of said basket.

Atty's 23150

1

2

Pat. App. Not known - US phase of PCT/EP2003/003532

- 8. (currently amended) Cooking device according to one or more of the previous claims claim 1, characterised in that said bowl is removably connected to said body.
- 9. (currently amended) Cooking device according to one
  cor more of the previous claims claim 1, characterised in that it
  comprises at least one third sensor of the presence of said bowl.
- 10. (currently amended) Cooking device according to one
  2 or more of the previous claims claim 1, characterised in that it
  3 comprises a closing cover applied on said basket.
- 11. (currently amended) Cooking device according to one
  2 or more of the previous claims claim 10, characterised in that said
  3 cover comprises at least one anti-foam door, free to oscillate from
  4 an open position to a closed position and vice-versa when the
  5 pressure inside said bowl exceeds a predetermined value.
- 1 12. (currently amended) Cooking device according to one
  2 or more of the previous claims claim 10, characterised in that said
  3 cover has a hole in which a container is housed suspended in said
  4 basket.
  - 13. (currently amended) Cooking device according to one or more of the previous claims claim 1, characterised in that said

Atty's 23150

Pat. App. Not known - US phase of PCT/EP2003/003532

- control means and said drive means are of the electromechanical
- 4 type.
- 1 14. (currently amended) Cooking device according to one
- or more of the previous claims claim 1, characterised in that said
- control means comprises a timer operatively connected to one or
- 4 more microswitches.
- 1 15. (currently amended) Cooking device according to one
- or more of the previous claims claim 1, characterised in that it
- comprises anti-rotation means for the pasta.
- 16. (currently amended) Cooking device according to one
- or more of the previous claims claim 15, characterised in that said
- anti-rotation means comprises a fixed anti-rotation element
- 4 connected to a fixed part of the device and inserted into said
- 5 basket and said bowl.
- 17. (currently amended) Cooking device according to one
- or more of the previous claims claim 16, characterised in that said
- fixed anti-rotation element has an end placed between trajectories
- 4 of said paddles.

Atty's 23150 Pat. App. Not known - US phase of PCT/EP2003/003532

- 18. (currently amended) Cooking device according to one
  2 or more of the previous claims claim 1, characterised in that said
  3 fixed element has a portion connected above said support.
- 19. (currently amended) Cooking device according to one
  cor more of the previous claims claim 1, characterised in that said
  drive group comprises a pin guide slidably connected to said basket
  and with a hole and a threaded lower portion, in said hole being
  inserted a pin with a blade suitable for connecting to a connection
  element of said first motor.
- 20. (currently amended) Cooking device according to one
  cor more of the previous claims claim 19, characterised in that said
  connection element comprises a disc which has a plurality of
  protruding pins and a hole in which a drive shaft of said first
  motor is slidably inserted, where a spring, which allows gaps to be
  closed, is placed between the casing of said first motor and said
  disc.
- 21. (original) Procedure for cooking through a device
  according to claim 1, characterised in that said heating means
  heats the water contained in the bowl taking it up to a
  predetermined temperature, at which point the first sensor detects
  that such a predetermined temperature has been reached and the
  basket is plunged into said water and, at the same time, the timer

1

- is started for a preset time period, at the end of which the
- s control means deactivates the heating means and commands the
- removal of the basket from said bowl.
- 22. (original) Procedure according to the previous
  claim, characterised in that after a predetermined period of time
  from the lowering of the basket into the bowl the stirring means is
  actuated.
- 23. (currently amended) Procedure according to one or more of claims claim 19 and thereafter, characterised in that said heating means is activated discontinuously, so as to partialise the power, to decrease the turbulence of the water and to reduce the production of foam.
  - 24. (currently amended) Procedure according to one or more of claims claim 19 and thereafter, characterised in that when the pasta is cooked at a predetermined time of day, said control means activates said heating means at a set time and checks the increase in temperature of the water and, in the case in which it is too fast, it interrupts the power supply to the electrical heating means and calculates the waiting time before starting to heat again.

## 25. (canceled)